

Changing to policyd-weight from postfix's built-in reject_rbl_client

Install a weighted RBL daemon for Postfix.

Last week my own server - hosting some sites from old and relatively close client - had been hijacked, and got listed on some RBL lists.

Using `apache2-mpm-itk` it was quite easy to trace it back, *because the spamsender process was running with a user's id, not with simple www-data*. Someone managed to log in with an FTP account, placed some scripts in the `www` directory, and started it from a web request. The real beauty was that the script removed itself after loading. It also sent the mails from the domain's default name, so, unfortunately it wasn't forged, and a lot of lists added my IP.

Using the help of `mxttoolbox.com`, a site for monitoring mailservers, a lot of hours and at least 10 apologizing mails I managed to remove myself. This reminded me, that I use the same method: RBL blockings right inside postfix's `main.conf`.

So if anyone got listed on one the lists I use, I reject their mail just like it happened to me. I clearly feel now, that this is not the good approach. So I looked for some kind of weighted possibility, like `spamassassin` for spam, and I met `policyd-weight`. It is the perfect tool I was looking for, and the best, Ubuntu has it as package.

```
apt-get install policyd-weight
```

```
bash
```

The only thing: it does not provide a default conf file, you need to create it with a build-in feature:

```
policyd-weight defaults > /etc/policyd-weight.conf
```

```
bash
```

You also need to add it to postfix's `main.conf`, right into `smtp_recipient_restrictions`

```
check_policy_service inet:127.0.0.1:12525,
```

```
bash
```

You can also remove every RBL entry from here after this is enabled.

Reload postfix

```
/etc/init.d/postfix reload
```

```
bash
```

and your system is ready to use policyd-weight, a lot more sophisticated solution for RBL listings, than built-in version of postfix.

To see more, visit Ubuntu manpage of policyd-weight^[^3], or the project's website^[^4].

Links

1. <http://tech.webportfolio.hu/4/installing-apache2-mpm-itk-on-a-virtualmin-based-ubuntu-8-04/>
2. <http://mxtoolbox.com>
3. <http://manpages.ubuntu.com/manpages/hardy/man8/policyd-weight.8.html>
4. <http://www.policyd-weight.org/>

Created by Peter Molnar <mail@petermolnar.net>, published at 2010-03-07 22:41 UTC, last modified at 2021-05-11 11:49 UTC , to canonical URL https://petermolnar.net/article/changing-to-policyd-weight-from-postfixs-built-in-reject_rbl_client/ , licensed under CC-BY-4.0 .